



550813

(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/086054 A1

(51) International Patent Classification⁷: **G01N 35/10,**
B41J 2/175

(21) International Application Number:
PCT/AU2004/000393

(22) International Filing Date: 29 March 2004 (29.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003901513 28 March 2003 (28.03.2003) AU

(71) Applicant (for all designated States except US): **PRO-
TEOME SYSTEMS INTELLECTUAL PROPERTY
PTY LTD** [AU/AU]; Unit 1, 35-41 Waterloo Road, North
Ryde, NSW 2113 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HOPWOOD, Femia**

[AU/AU]; 8 Marconi Street, Winston Hills, NSW 2153
(AU). **GOOLEY, Andrew, Arthur** [AU/AU]; 15 Katina
Street, Turramurra, NSW 2074 (AU).


(74) Agent: **F B RICE & CO**; 605 Darling Street, Balmain,
NSW 2041 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: APPARATUS FOR DISPENSING AND PRINTING FLUIDS



(57) Abstract: A piezoelectric dispensing apparatus (10) includes a piezoelectric dispensing device (20) including a fluid reservoir (20a) and a piezoelectric dispensing tube (70). The apparatus includes a seat for receiving the device and a plunger which is shaped and configured to abut with and seal the top of the reservoir and which defines a through bore to permit the application of vacuum and or pressure to the reservoir through the bore. The plunger may be moved up and down towards and away from the seat. The fluid reservoir defines an open top and an outlet at the base of the reservoir closed by a filter. The base of the reservoir define a foot. A secondary filter assembly is attachable to the base of the reservoir. The secondary filter assembly defines a bore which is in fluid communication with the reservoir when the secondary filter assembly is attached thereto. The secondary filter assembly also defines means for removably attaching the piezoelectric dispensing tube in fluid communication with the bore. The device includes a ducks bum valve or septum for closing the outlet of the reservoir until the reservoir is attached to the removable secondary filter assembly.

WO 2004/086054 A1



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*